



NOTES:
 1. ALL RESISTOR VALUES ARE IN OHMS, 1/4W 5%, UNLESS OTHERWISE SPECIFIED.
 2. CAPACITORS MARKED IN DECIMAL VALUES ARE IN μ F. CAPACITORS MARKED IN WHOLE NUMBER VALUES ARE IN μ F TAKEN WITH A HIGH IMPEDANCE VOLTMETER AND A REFERENCE RESISTOR BRIDGED TO GROUND.
 3. REFER TO RESISTOR BAND FOR GROUND AND SIGNAL INPUT.
 4. TITLES IN RECTANGLES INDICATE FRONT PANEL NOMENCLATURE.
 5. SWITCHES ARE SHOWN IN FULL CLOCKWISE POSITION.
 6. ABBREVIATIONS:
 AND ARE VIEWED FROM FRONT PANEL.
 K - 1000
 M - 1,000,000
 TANT - TANTALUM 35V

POSITION	FUNCTION	RANGE	S2
1	-DC V	500M, 500A, 100W/P, R, 0.1	
2	AC V	150M, 150A, 420M/P, R, 1	
3	AC I	150M, 150A, 420M/P, R, 100	
4	HI OHMS	15V, 15mA, 42 VP-P, R, 100	
5	LO OHMS	15V, 15mA, 4VP-P, R, 10K	
6	ACA	15V, 15mA, 42VP-P, R, 10K	
7	DCA	50V, 50mA, 140VP-P, R, 100K	
8		150V, 150mA, 420VP-P, R, 1M	
9		600V, 500MA, 1400VP-P	
10		1500V, 1500MA, 4200VP-P	

LAST NUMBER USED	NOT USED
R71	R, 53.3K
C28	DS
D10	DS
Q4	
T1	
M1	
F2	
S02	
S3	
T1	

* INDICATES VARIANCE DEPENDING ON Q3