

SPECIFICATIONS**1502**

Description: 1.5V/3V/4.5V/6V/9V/12V 0.5A Power Supply
Input Voltage: 115VAC 60Hz
Environment Temperature: 25C°

| | MIN. | TYP. | MAX. | UNIT |
|--|-------------|-------------|-------------|-------------|
| Output Voltage 1.5V | 1.3 | | 1.8 | V |
| Output Voltage 3V | 2.6 | | 3.4 | V |
| Output Voltage 4.5V | 4.2 | | 3.4 | V |
| Output Voltage 6V | 5.5 | | 6.4 | V |
| Output Voltage 9V | 8.5 | | 9.4 | V |
| Output Voltage 12V | 11.5 | | 12.5 | V |
| Output Current | | 0.5 | | A |
| Voltage Regulation: | | | | |
| Load (0-100% Load) | | | 120 | mV |
| Line (110-130VAC Variation) | | | 300 | mV |
| Ripple & Noise | | | 200 | mVp-p |
| No Load Input Current | | | 80 | mA |
| Full Load Input Current (All Rated Load) | | | 180 | mA |
| Fuse 1 | | 2 | | A |
| Fuse 2 | | 0.5 | | A |

Dimensions (W X D X H): 4.33 x 5.51 x 3.27"

Weight: 2.43 lbs.

Operation:

Plug model 1502 into AC outlet. Turn power switch on, power light will come on.
 Adjust control knob to desired voltage.