ManualsPlus.com

CRT ADAPTER

BK PRECISION®

MODEL CR-38

WIRING SCHEME		
CRT SOCKET PIN	WIRE COLOR	NYLON RECEP-TACLE
1	WHT	12
2	—	—
3	keyway	—
4	BLU	3
5	WHT/BLU	9
6	BLK	1
7	BRN	2
8	YEL/RED	8
9	RED	4
10	WHT/RED	7
11	—	—
12	YEL/GRN	6
13	GRN	5
14	keyway	—

FITS CRT DIMENSIONS:

A = pin circle diameter = 15.24 mm/0.600" nom.
a = angular pin spacing = 25-5/7°
B = post diameter = 11.4 mm/0.449" max.
C = keyway width = 2.00 mm/0.079" max.
D = keyway depth = 4.25 mm/0.167" max.

BK PRECISION®

B & K-Precision, Factory Service Department
Maxtec International Corporation
6470 West Cortland Street
Chicago, Illinois 60635
Telephone: (312) 889-1448

481-167-9-038B

ManualsPlus.com

Used with **B & K-Precision** Models: 467, 470, 480, 490.

TUBE TYPE	HEATER VOLTAGE
680CB22	6.3
680EB22	6.3
680FB22	6.3
A64JKB00X	6.3
A64JKJ00X	6.3
A64JKJ10X	6.3
A64JKJ11X	6.3
SD116-B #	6.3
SD116-G #	6.3
SD116-R #	6.3

Tubes marked with (#), Red and Green guns interchanged (test Red gun with Green controls, and vice versa).

In order to keep your set-up chart up-to-date, it is recommended that you subscribe to the **B & K-Precision** chart mailing service. These mailings will occur in May and November of each year and will include all the tubes presently listed on your chart plus all new types of CRT's that have come out since the last mailing.

If you wish to take advantage of this service, contact:

B & K-PRECISION, FACTORY SERVICE DEPARTMENT
MAXTEC INTERNATIONAL CORPORATION
6470 West Cortland Street
Chicago, Illinois 60635
Telephone #: (312) 889-1448

For information on ordering a subscription.

BK PRECISION®

ManualsPlus.com

ManualsPlus.com