


ALIGNMENT PROCEDURE
SUPER SKYRIDER
Models S-16 SX-16






the halli-crafters *co.*
CHICAGO

SCHEMATIC DIAGRAM - SUPER SKYRIDER - TYPE SX-16




The Hallicrafters Inc. Chicago, U.S.A.	
Name Super Sky Rider	
Model SX-16	
Drawn by R.J.H.	Date 5-17-37
Checked by [Signature]	Approved by [Signature]
Revisions 6-1B-37	
7/15/37	



ALIGNMENT PROCEDURE FOR SUPER-SKYRIDER MODELS S-16, SX-16

THE FOLLOWING MEASUREMENTS MADE WITH 1000 OHMS PER VOLT METER AND TAKEN FROM THE POINT INDICATED TO GROUND. ANTENNA AND GROUND DISCONNECTED AND R. F. AND A. F. GAIN CONTROLS SET AT MAXIMUM. LINE VOLTAGE OF 115 AT TIME MEASUREMENTS WERE TAKEN. NORMAL TOLERANCE ALLOWS VARIATION PLUS OR MINUM 10% FROM VALUES INDICATED. "DL" INDICATES DEAD LUG BUT WILL INDICATE VOLTAGE WHEN USED AS A TIE.



BOTTOM VIEW OF SOCKET

TUBE	FUNCTION	1	2	3	4	5	6	7	8
6K7	R.F. AMP.			275	110	7	0 ON 60 OFF	6.3	7
6L7	MIXER			275	100	0	DL	6.3	2.5
6J5G	Osc			180	DL	0	DL	6.3	0
6K7	IF AMP (1)			270	110	6.5	DL 140	6.3	9
6K7	IF AMP (2)			270	110	6.5	0 ON 60 OFF	6.3	9
6R7G	2ND DET. A.V.C.			190	4.5	4.5	0	6.3	-7
6V6G	1ST AUDIO OUTPUT			315	275	0	DL	6.3	14.5
6V6G	OUTPUT			315	275	0	DL	6.3	14.5
6J7	BEAT Osc.			150	150	0	DL 300	6.3	0
6J7G	Sig. AMP.			275	110	5	DL 300	6.3	8

INTERMEDIATE FREQUENCY ALIGNMENT (465KC)

HAVE THE CONTROLS SET IN THE FOLLOWING POSITIONS:

- B.F.O. INJECTOR "OFF"
- A.F. AND R.F. GAIN CONTROLS ON FULL.
- SELECTIVITY SWITCH ON "SHARP" POSITION.
- CRYSTAL PHASING CONDENSER MIDWAY (POINTER STRAIGHT UP).
- A.V.C. SWITCH "OFF".
- CRYSTAL SWITCH "IN".

(IF ALIGNMENT CONTINUED)

BAND SWITCH ON #1 BAND - TUNING GANG OPEN.
 REMOVE OSCILLATOR TUBE.
 REMOVE 6L7 GRID CAP.
 CONNECT SIGNAL GENERATOR TO GRID OF 6L7 TUBE THROUGH A .1 MFD CONDENSER. TUNE SIGNAL GENERATOR TO 465 KC AND THEN ADJUST THE FOLLOWING TRIMMERS FOR MAXIMUM OUTPUT: T4-#7,8; T3-#5,6; T2-#3,4; T1-#1,2; THROW CRYSTAL SWITCH TO "OUT" POSITION AND READJUST TRIMMERS # 2, 3 FOR MAXIMUM OUTPUT. WHEN THE "SELECTIVITY" SWITCH IS SNAPPED INTO THE "BROAD" POSITION A SLIGHT DROP IN GAIN SHOULD BE INDICATED. A RECTIFIER TYPE METER IS SUGGESTED AS OUTPUT INDICATOR.

ALIGNMENT USING 465 KC CRYSTAL

SHOULD THE RECEIVER BE A CRYSTAL MODEL IT IS NECESSARY THAT THE CRYSTAL BE USED IN AN EXTERNAL OSCILLATOR IN PLACE OF A SIGNAL GENERATOR SUCH AS THE ABOVE. THE OUTPUT OF THIS CRYSTAL CONTROLLED OSCILLATOR IS THEN FED TO THE GRID OF THE 6L7 TUBE AND THE ABOVE PROCEDURE FOLLOWED. WHEN THE IF AMPLIFIER HAS BEEN ALIGNED FROM THE CRYSTAL OSCILLATOR'S OUTPUT, RE-INSERTING THE CRYSTAL IN THE RECEIVER WILL SHOW VERY LITTLE DIFFERENCE IN OUTPUT WHETHER THE CRYSTAL IS "IN" OR "OUT" OF THE CIRCUIT AS INDICATED BY THE CRYSTAL SWITCH.

R. F. ALIGNMENT PROCEDURE

ON BAND #1, OR BROADCAST, USE A .0002 MFD CONDENSER IN SERIES WITH OUTPUT LEAD FROM GENERATOR TO RECEIVER. ON THE OTHER BANDS USE A 400 OHM RESISTOR. BE SURE JUMPER FROM DOUBLET POST TO GND. REMAINS CONNECTED WHEN ALIGNING THE RECEIVER.
 ALL PAD ADJUSTMENTS (LOCATED ON THE TOP OF THE CHASSIS) ARE FOR THE LOW FREQUENCY ENDS OF THE BANDS.
 ALL TRIMMER ADJUSTMENTS (LOCATED ON THE BOTTOM OF THE CHASSIS) ARE FOR THE HIGH FREQUENCY ENDS OF THE BANDS.
 REDUCE R.F. GAIN CONTROL BELOW THE POINT OF BLOCKING OR OVERLOADING; ALSO BE SURE THAT THE CRYSTAL SWITCH IS IN THE "OUT" POSITION AND THE A.V.C. SWITCH IS IN THE "OFF" POSITION.
BE SURE TO CHECK IMAGES - IMAGES WILL FALL A LITTLE LESS THAN 1000 KC LOWER IN FREQUENCY THAN THE FUNDAMENTAL OR HARMONIC OF SIGNAL.

THE TUNING GANG MUST BE ROCKED WHEN MAKING THESE ADJUSTMENTS.

NOTE #1 HARMONICS OF SUITABLE FREQUENCIES MAY BE USED IF THE FOLLOWING FREQUENCIES SUGGESTED ARE NOT AVAILABLE.

" #2 IT IS NECESSARY TO REPEAT EACH PAIR OF OPERATIONS SEVERAL TIMES UNTIL NO CHANGE IS NOTED.

OPR.	BAND	RECEIVER DIAL SETTING	SIGNAL GENERATOR FREQUENCY	ADJUST Osc. WITH	TRIMMERS ADJ. FOR MAX GAIN	ADJUST Osc. WITH	PADDERS ADJ. FOR MAX GAIN
1 2	1 1	600kc 1400kc	600kc 1400kc	----- CA	----- CB - Cc	C9 -----	----- -----
3 4	2 2	1800kc 4000kc	1800kc 4000kc	----- Cd	----- CE - CF	C8 -----	----- -----
5 6	3 3	5000kc 9000kc	5000kc 9000kc	----- Cg	----- CH - CI	C6 -----	C14 - C10 -----
7 8	4 4	10,000kc 18,000kc	10,000kc 18,000kc	----- CJ	----- CK - CL	C7 -----	C15 - C11 -----
9 10	5 5	20,000kc 30,000kc	10,000kc 10,000kc	----- CM	----- CN - Co	C5 -----	C16 - C12 -----
11 12	6 6	40,000kc 60,000kc	20,000kc 20,000kc	----- CP	----- Cq - CR	C4 -----	C17 - C13 -----

SERVICING SUGGESTIONS

TO MAKE A RAPID CHECK OF THE RECEIVER REMOVE GRID CAP OF THE 6R7 TUBE AND TOUCH THE GRID OF THE TUBE WITH YOUR FINGER. IF A LOUD HUM IS HEARD THE AUDIO END OF THE RECEIVER IS OK.

DEAD SET. CHECK BIAS OF THE R.F. TUBES. IF THE BIAS IS TOO HIGH CHECK THE R.F. GAIN CONTROL FOR AN OPEN. ADDITIONALLY, CHECK THE PLATE AND SCREEN VOLTAGE OF THE R.F. TUBES - (SEE CHART). CHECK "BPLUS" FOR A SHORT TO GROUND - IF SO CHECK ALL TUBES.

IF THE RECEIVER DEVELOPS A HIGH-PITCH AUDIO SQUEAL REVERSE THE GRID WIRES OF THE AUDIO INPUT TRANSFORMER.

NOISY GANG WHEN JARRED - INCREASE THE TENSION ON THE GANG WIPERS.

NOISY COIL ASSEMBLY - LIGHTLY TAP THE TRIMMERS OF THE PARTICULAR BAND IN WHICH NOISE OCCURS. ONCE LOCATED THE TRIMMER SHOULD BE REPLACED.

IF LOW SIGNAL AND HIGH NOISE LEVEL DEVELOPS REPLACE THE 6L7 TUBE.

DEAD BEAT OSCILLATOR - IF 6J7 SHOULD SHORT TO GROUND IT WILL OPEN THE B0 CONTROL. CHECK #1 - "BPLUS" TO B0 COIL FOR A GROUND. CHECK #2 - CHECK THE B0 INJECTION CONTROL FOR AN OPEN CIRCUIT. IN MOST CASES A NEW 6J7 WILL CORRECT A DEAD B0.

VIOLENT OSCILLATION - CHECK ALL 6K7 TUBES. ALSO IF A 300 OHM BIAS RESISTOR IS USED ON THE LAST 6K7 IF AMPLIFIER REPLACE WITH A 400 OHM RESISTOR.

LIST OF RESISTORS SUPER-SKYRIDER MODELS S-16, SX16

No.	OHMS	WATTAGE	PARTS No.	No.	OHMS	WATTAGE	PARTS No.
R1	100,000	1/5	20-093	R18	100,000	1/5	20-093
R2	5,000		25-021	R19	1,000,000	"	20-108
R3	10,000	2.5	24-037	R20	1,000	"	20-033
R4	10,000	"	24-037	R21	1,000,000	"	20-108
R5	700	1/5	24-038	R22	20,000	"	20-072
R6	50,000	"	20-084	R23	100,000	"	20-099
R7	10,000	1.	20-061	R24	100,000	"	20-099
R8	100,000	1/5	20-093	R25	950	"	22-032
R9	285	"	22-020	R26	1,000,000	"	25-023
R10	29,000	1.	22-075	R27	20,000	"	20-072
R11	50,000	1/5	20-084	R28	1,000,000	"	25-013
R12	50,000	"	20-084	R29	10,000	"	20-063
R13	50,000	"	20-084	R30	500		25-022
R14	500,000	"	25-024	R31	95	1/2	22-007
R15	100,000	"	20-093	R32	235	1.	22-015
R16	380	"	22-021	R33	1,000	1/5	20-033
R17	100,000	"	20-093				

LIST OF CONDENSERS SUPER-SKYRIDER MODELS S-16, SX-16

No.	CAPACITY	TYPE	VOLTAGE	PARTS No.	No.	CAPACITY	TYPE	VOLTAGE	PARTS No.
C1	420 MMFD	MAIN			C32	.01 MFD			41-001
C2	420 "	"			C33	.01 MFD			41-001
C3	420 "	GANG			C34	.05 "			41-005
C4	100 "	"			C35	.05 "			41-004
C5	100 "	"			C36	.1 "			41-007
C6	310 "	"			C37	.05 "			41-004
C7	880 "	"			C38	100 MMFD	MICA		40-007
C8	1,400 "	"			C39	100 "	"		40-007
C9	590 "	"			C40	10 MFD	ELEC	25	42-002
C10	1,000 "	"			C41	.0005 "	MICA		43-008
C11	350 "	"			C42	.005 "	"		45-003
C12	180 "	"			C43	.02 "	"		41-003
C13	120 "	"			C44	16 "	"		42-019
C14	1,000 "	"			C45	16 "	"		42-019
C15	350 "	"			C46	1 "	"		41-013
C16	180 "	"			C47	.01 "	"		41-001
C17	120 "	"			C48	50 MMFD	"		40-002
C18	.002 MFD	MICA			C49	250 "	MICA		40-007
C19	.05 "	"	200		C50	.05 MFD	"	400	41-005
C20	.1 "	"			C51	10 MMFD	"		40-021
C21	.002 "	"	400		C52	10 "	"		40-021
C22	100 MMFD	"			C53	10 "	"		40-021
C23	.05 MFD	"	200		C54	10 "	"		40-021
C24	.25 MMFD	AIR			C55	50 "	"		40-002
C25	.002 MFD	MICA			C56	10 "	"		40-021
C26	.05 "	"	200		C57	10 "	"		40-021
C27	.05 "	"	400		C58	10 "	"		40-021
C28	.25 MMFD	AIR			C59	25 "	"		40-024
C29	.05 MFD	"	200		C60	.05 MFD	"	200	41-004
C30	.25 "	"	200		C61	.05 "	"	200	41-004
C31	10 MMFD	MICA			C62	.002 "	"		40-013
					C63	.002 "	"		40-013

S1 CRYSTAL SWITCH SPST
 S2 BEAT OSC. SWITCH ON B. F. O. INJECTION CONTROL
 S3 A. V. C. SWITCH DPST
 S4 SEND-RECEIVE SWITCH SPST
 S5 A. C. SWITCH ON TONE CONTROL
 S6 METER SWITCH ON R. F. GAIN CONTROL
 S7 SELECTIVITY SWITCH DPDT