ManualsPlus.com

WWW.VINTAGE-RADIO.INFO

WAVEFORMS







NOTE: IC322 IS USED AS A VARIABLE RESISTOR; THEREFORE NONE OF ITS PINS ARE TIED TO +11.4V OR GROUND.











SCHEMATIC OF THE HEATHKIT® ELECTRONIC CLOCK CHIMES MODEL GCA-1195-1

Copyright © 1976
Heath Company
All Rights Reserved
Printed in the United States of America

Part of 595-1896



NOTES:

1. ALL RESISTORS ARE 1/2-WATT, UNLESS MARKED OTHERWISE. VALUES ARE SHOWN IN OHMS (K=1,000, M=1,000,000).
2. CAPACITOR VALUES ARE SHOWN IN MICROFARADS, UNLESS MARKED OTHERWISE.
3. SYMBOLS: ☐ LETTERED CIRCUIT BOARD HOLE.
   ▽ CIRCUIT BOARD GROUND.
   ▽ WAVEFORM.
4. WAVEFORM J IS TYPICAL OUTPUT OF IC'S IN NOTE FREQUENCY SYNTHESIZER.
5. WAVEFORM L IS TIC-TOC SYNTHESIZER OUTPUT.
6. WAVEFORM S IS EXPANDED VIEW OF A SINGLE CHIME NOTE.
7. WAVEFORM T IS COMPOSITE VIEW OF A SINGLE CHIME NOTE.